

Precision scale

Precision scales (10 mg) which combines beautiful and robust design with great functionality and easy use through the guide of the menus on display.



FEATURES:

- » LCD backlight display, excellent display, with advanced eye protection.
- » 8 digits of 15 mm in display with messages as a way to guide the user.
- » 7 keys of direct functions.
- » Superior frame in ABS and pan in stainless steel.
- » Scale with a metal housing robust frame, for the protection against the causes of electrical storms and electromagnetic interferences.
- » Four adjustable feet. They allow a greater stability, giving more precise results.
- » Bubble level.
- » Time of answer: 2-3 seconds.
- » Multiple units of measure: gram, kilogram, pound, ounce, troy ounce, grain, pennyweight, carat, milligram, momme, mesghal, Hong Kong tael, Singapore taels, Taiwan taels, bath.
- » Under weighing.
- » Operating temperatura range: +15°C +30°C.
- » Available models with internal calibration (HL-I).
- » RS232, PC format and printer.
- » 3 type of data sending to PC:
 - Continue: data sending in continue mode.
 - Ald: data sending to PC in stabilized weight.
 - Req: data sending to PC by user request.
- » GLP/GMP.
- » It is included dust cover and blister.
- » Weighing system with electromagnetic compensation block.



FUNCTIONS

- » Piece counting
- » Determination of percentage
- » Filter of weighing of animals
- » Formulation
- » Custom unite
- » Control of weight
- » Function of target weighing
- » Determination of density
- » Calibration of the pipette
- » Statistics
- » Totalization



RS232, Dual Display y Foot



Bubble level



Adjustable feet

Precision	260346	260348	260347	260349
Type of cabin scale	-			
Multiple units	Yes			
CE regulations	Yes	Yes	Yes	Yes
Formulation	Max. number of weights that can be summed is 99			
Type of calibration	External	External	Internal	Internal
Auto calibration	no	no	Yes	Yes
Mass of calibration (g)	1500 (F1)	2000 (F1)	1500 (F1)	2000 (F1)
Class	II	II	II	II
Net weight (kg)	4,8			

Code #	Internal calibration	Capacity (g)	Readout (g)	Pan dimensions (mm)	Packing dimensions (mm)	Packing weight (kg)	Certifications
							ENAC Code #
260346		3100	0,01	198x205	500x410x330	7,5	901011
260348		4100	0,01	198x205	500x410x330	7,5	901011
260347		3100	0,01	198x205	500x410x330	7,5	901011
260349		4100	0,01	198x205	500x410x330	7,5	901011

Accessories

Code #	Accessories description
-	Printers